

Typical Glazing Specification:
 White polyester powder coated aluminium lid
 backed with 16mm thick structured polycarbonate

X2V ROOFLIGHT SPECIFICATION

(FABRICATED FROM SELF FINISH WHITE EXTRUDED uPVC)

Quantity of Rooflight(s)	1no
Roof Opening - Length (mm)	Dim A
Roof Opening - Width (mm)	Dim B
Roof Insulation Depth (mm)	Dim C
Kerb Ventilation?	x
Opening Frame? (Gas spring operated)	✓

STRUCTURED POLYCARBONATE BACKED LID, POLYESTER POWDER COATED WHITE, POP RIVETED TO uPVC KERB

uPVC WEATHER FLANGE; REMOVE, APPLY WEATHER PROOFING MEMBRANE TO KERB, AND RE-FIT WITH FIXINGS PROVIDED

ROOF FINISHES DRESSED UP EXTERNAL FACE OF X2V KERB BY ROOFING CONTRACTOR

X2V KERB SECURED USING SUITABLE FIXINGS @ 300mm CENTRES (FIXINGS BY INSTALLER)

2No. GAS SPRINGS

LOCKING HANDLE

RESTRAINING CORDS

MINIMUM 150

Dim C ROOF INSULATION DEPTH

60 Dim A - ROOF OPENING LENGTH 60

60 Dim B - ROOF OPENING WIDTH 60

SECTION THROUGH LENGTH

SECTION THROUGH WIDTH

REV:	DATE:	DESCRIPTION:	DRN BY	DESCRIPTION:
0	12.09.16	First issue of this drawing	DL	Unventilated vertical uPVC access hatch fixed direct to roof with 120mm uPVC extension piece (for flat roof insulation), with gas sprung opening frame (with restraining cords), and insulated solid lid.
DRAWN BY:		CREATION DATE:	CHECKED BY:	SCALE(S)
DL		12.09.16	--	1:5 @ A3
REVISION:		0		
Rooflights & Glazing Unit 5, Ironbridge Industrial Estate, 397 Retford Road, Sheffield, S13 9WA T:0114 408 1000 F:0114 238 5511 E:sales@rooflightsandglazing.co.uk W:www.rooflightsandglazing.co.uk				

ROOFLIGHTS & GLAZING

DRG No.
RG-X2V-A-04G-ISL